

PM95LWS

PARVALUX®



MOTOR	Permanent magnet DC motor
PROTECTION	Totally enclosed (IP54)
GEARBOX	Worm spur (LWS)
MOTOR POWER	168 - 525 Watts
SPEED	0.4 - 80 rpm
VOLTAGE	12V, 24V, 36V or 48V, D.C.
WEIGHT	8.9 kg
RADIAL LOAD	446 N
AXIAL LOAD	226 N
SHAFT TYPE	Single ended or double ended shaft as standard; 17mm diameter shaft available with ratios 115:1 and 56:1
EXTRAS	Gearbox available without feet; unit can be mounted on gearbox spigot; for further options see page 36

See page 158 to specify shaft and gearbox position

Motor Power Cont (W)	168	225	337	450	TORQUE (Nm)			
Motor Power 1 Hour (W)	210	281	421	563				
Motor Power 15 Min (W)	294	394	590	525				
Ratio Worm	Ratio Spur	MOTOR SPEED (rpm)				CONTINUOUS	1 HOUR	15 MINUTE
		1500	2000	3000	4000			
		OUTPUT SPEED (rpm)						
30	115	0.4	0.6	0.9	1.2	100	100	100
16 1/2	115	0.8	1.1	1.6	2.1	100	100	100
8 1/3	115	1.6	2.1	3.1	4	100	100	100
7 1/4	115	1.8	2.4	3.6	5	100	100	100
12 1/2	56	2.1	2.9	4.3	6	100	100	100
10 1/3	56	2.6	3.5	5.2	7	100	100	100
9 1/3	56	2.9	3.8	5.7	8	100	100	100
8 1/3	56	3.2	4.3	6.4	9	100	100	100
7 1/4	56	3.7	4.9	7.4	10	100	100	100
6 1/4	56	4.3	5.7	8.6	11	100	100	100
13 1/2	25	4.4	5.9	9	12	62	62	62
12 1/2	25	4.8	6.4	10	13	62	62	62
10 1/3	25	5.8	8	12	15	62	62	62
9 1/3	25	6.4	9	13	17	62	62	62
8 1/3	25	7	10	14	19	62	62	62
6 1/4	25	10	13	19	26	62	62	62
16 1/2	6	15	20	30	40	32	32	32
13 1/2	6	19	25	37	49	32	32	32
11 1/3	6	22	29	44	59	32	32	32
9 1/3	6	27	36	54	71	32	32	32
8 1/3	6	30	40	60	80	32	32	32

